

(19) World Intellectual Property Organization  
International Bureau(43) International Publication Date  
17 January 2002 (17.01.2002)


PCT

(10) International Publication Number  
WO 02/05059 A2

- (51) International Patent Classification<sup>7</sup>: G06F
- (21) International Application Number: PCT/US01/21188
- (22) International Filing Date: 3 July 2001 (03.07.2001)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 60/216,640 7 July 2000 (07.07.2000) US
- (71) Applicant (for all designated States except US): BAXTER INTERNATIONAL INC. [US/US]; One Baxter Parkway, Deerfield, IL 60015 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): CORK, William H. [US/US]; \*\* (\*\*). ULMES, James, J. [US/US]; \*\* (\*\*). WEST, Richard, L. [US/US]; 37162 North Lake Shore Drive, Lake Villa, IL 60046 (US). LO, Ying-Chen [US/US]; 225 Fox Run Road, Green Oaks, IL 60048 (US). WEBER, Mark, C. [US/US]; 800 Birch Street, Algonquin, IL 60102 (US). MIN, Kyungyoon [KR/KR]; 7267 Clem Drive, Gurnee, IL 60031 (US).
- (74) Agents: PRICE, Bradford, R., L.; Baxter Healthcare Corporation, Route 120 and Wilson Road, Round Lake, IL 60073 et al. (US).
- (81) Designated States (national): AU, BR, CA, CH, CN, DE, ES, GB, IN, JP, MX, US.
- (84) Designated States (regional): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).

[Continued on next page]

## (54) Title: MEDICAL SYSTEM, METHOD AND APPARATUS EMPLOYING MEMS



(57) Abstract: A biological suspension processing system is disclosed that may include a suspension treatment device for treating one or more components of a biological suspension, a first fluid flow path for introducing a suspension into the treatment device and a second fluid flow path for withdrawing a constituent of the suspension from the device. At least one micro-electromechanical (MEM) sensor communicates with one of the fluid flow paths for sensing a selected characteristic of the fluid therewith. The MEM sensor may be located elsewhere, such as on a container or bag and communicate with the interior for sensing a characteristic of the fluid contained therein. A wide variety of characteristics may be sensed, such as flow rate, pH, cell type, cell antigenicity, DNA, viral or bacterial presence, cholesterol, hematocrit, cell concentration, cell count, partial pressure, pathogen presence, or viscosity.

WO 02/05059 A2